

ateljé Lyktan



# STOCKHOLM 370

Design by Olle Anderson







**Black / Grey**  
RAL9005 G72 / RAL9006

## Technical specifications

<b>Material</b>	Body and shades in aluminium. Clear toughened acrylic disc.
<b>Installation</b>	For mounting on wall.
<b>Connection</b>	Terminal block 3x2.5 mm <sup>2</sup> .
<b>Diffuser</b>	White-painted interior to lower shade.
<b>Light source</b>	230V light source with E27 socket, must be ordered separately.
<b>Light scattering</b>	Symmetrical.
<b>Weight</b>	3.7 kg
<b>Corrosivity category</b>	Our outdoor products are in their standard performance painted for environments corresponding to corrosivity category C3. Can be used in environments like urban and industrial atmospheres with a moderate sulphur dioxide pollution or areas with some influence from the coast. For environments with a high sulphur dioxide pollution, we can offer a special treatment for higher corrosive resistance. This will be quoted on request.
<b>Energy classification</b>	This product contains a light source of following efficiency class: Light source with CRI and CT 830/840 - Class E

# ateljé Lyktan

Head Office

Fyrvaktaregatan 7, SE-296 81 Åhus, Sweden

Tel: +46 (0)44 28 98 10

E-mail: [info@ateljelyktan.se](mailto:info@ateljelyktan.se)

[www.ateljelyktan.se](http://www.ateljelyktan.se)